


GP500/1000

GP Series is specially designed for PC users. This series is also suitable for use with computer peripherals or POS and will become an attractive piece of equipment in the office or at home. Committed to EAST's objective of 'Quality First', the GP Series adopts the latest SMD technology plus EAST's on-line UPS high frequency technology to achieve a technical breakthrough of 40 KHz operating frequency. Its dimensions and weight have been reduced dramatically. Besides its space-saving compact size, these UPSs also impress you with their elegant appearance. The one-piece plastic housing in asymmetric streamlined design adds to the convenience for use by individual and home users.

<p><u>APPLICATION</u></p> <p>PCs, POS Systems</p> <p>KEY FEATURES</p> <ul style="list-style-type: none"> ● Ultra slim design with ultra light weight ● Compact Size with comprehensive features ● Simple and easy operation ● Self diagnosis while being powered on and self monitoring ● Safe charger to lengthen the life span of the battery 	
--	--

SPECIFICATIONS

Product Series		GP series	
Model		GP500	GP1000
Rated Power		500VA/300W	1000VA/600W
Input	Nominal Voltage	220VAC	
	Voltage Range	165~265VAC	
Output on Battery	Voltage	220Vrms ±10%	
	Frequency	50Hz ±1Hz	
Battery	Type	Sealed Lead-Acid, Maintenance-free	
	Capacity	12V7Ah*1	12V7Ah*2
	Back-up time (half load)	≥ 7 min	
	Recharge time	10 hrs max.	
LED indicators	Status	Normal , Back up, Battery low, Fault	
Audible alarm	Battery discharge	Beeping sound every four seconds after utility power fails. Every second if battery approaches	

		final discharge	
	Fault	Continuous beeping sound	
Output receptacles	Type	IEC320 or NEMA5-15R	NEMA5-15R
	Quantity	2 pieces	3 pieces
Environmental	Operating Temperature	0 ~ 40 °C	
	Relative Humidity	20% ~ 90% non-condensing	
Weight	Net/Gross (kg)	3.3/3.9	6.5/7.0
Dimensions	W x D x H (mm)	80 x 230 x 177	91 x 280 x 238

Specifications are subject to change without prior notice